

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A sputtering target transport box ~~having a void the size of a sputtering target~~, comprising:

a plate-shaped sputtering target;

[an] a rigid inner sputtering target retention frame defining a void the size of [a] said sputtering target, said sputtering target being positioned in said void within said retention frame, and said retention frame preventing movement of said sputtering target relative to said retention frame;

a rigid plastic inner box having a lower plate and an upper plate, said retention frame being positioned within said inner box between said lower and upper plates such that movement of said retention frame and sputtering target relative to said inner box is prevented;

[an] a separate rigid outer box formed of aluminum or wood and having an outer frame, a bottom plate, and a cover providing an inner size that is greater than said inner box, the inner box charged with the sputtering target is further placed in insertable within the outer box for transport ,the inner box may be and is independently removed removable from the outer box for transport; and

rigid stationary supports for mechanical transport extend from the bottom plate of said transport outer box and wheels for man-powered transport are

provided adjacent [an] only a rear edge portion of said bottom plate and not adjacent an opposite front edge of said bottom plate, the height of the supports is greater than the height that each of the wheels extends from the bottom plate of the outer box such that the outer box is supported on an underlying surface via said supports when the bottom plate extends parallel to the underlying surface and such that the outer box is supported on said wheels only when the bottom plate of the outer box is inclined relative to the underlying surface.

Claims 2-10 (canceled).

Claim 11 (currently amended): A sputtering target transport box according to claim 1, wherein a handle is mounted on a side face or the bottom plate of the outer box opposite the ~~wheel~~ wheels, and wherein the transport box is inclined during transport when utilizing the handle such that the transport box is supported on the ~~wheel~~ wheels and the supports do not interfere with a floor face.

Claim 12 (previously presented): A sputtering target transport box according to claim 11, wherein a resin or wood material is affixed to respective faces of the periphery, corners and supports of the outer box to cushion impact with the floor face of a building.

Claim 13 (previously presented): A sputtering target transport box according to claim 12, wherein a conductive thin film is affixed to an outer surface of the outer box to prevent electrification.

Claim 14 (currently amended): A sputtering target transport box according to claim 13, wherein a through-type hold is provided on the inner box to simplify removal of said inner box from said outer box.

Claim 15 (previously presented): A sputtering target transport box according to claim 14, wherein a cushion material is provided between the outer box and inner box.

Claim 16 (previously presented): A sputtering target transport box according to claim 15, further comprising a joint removably fixing the cover of the outer box to the outer frame of the outer box.

Claim 17 (previously presented): A sputtering target transport box according to claim 1, wherein a resin or wood material is affixed to respective faces of the periphery, corners and supports of the outer box to cushion impact with the floor face of a building.

Claim 18 (previously presented): A sputtering target transport box according to claim 17, wherein a conductive thin film is affixed to an outer surface of the outer box to prevent electrification.

Claim 19 (currently amended): A sputtering target transport box according to claim 18, wherein a through-type hold is provided on the inner box to simplify removal of said inner box from said outer box.

Claim 20 (previously presented): A sputtering target transport box according to claim 19, wherein a cushion material is provided between the outer box and inner box.

Claim 21 (previously presented): A sputtering target transport box according to claim 20, further comprising a joint removably fixing the cover of the outer box to the outer frame of the outer box.

Claim 22 (previously presented): A sputtering target transport box according to claim 1, wherein a conductive thin film is affixed to an outer surface of the outer box to prevent electrification.

Claim 23 (currently amended): A sputtering target transport box according to claim 22, wherein a through-type hold is provided on the inner box to simplify removal of said inner box from said outer box.

Claim 24 (previously presented): A sputtering target transport box according to claim 23, wherein a cushion material is provided between the outer box and inner box.

Claim 25 (previously presented): A sputtering target transport box according to claim 24, further comprising a joint removably fixing the cover of the outer box to the outer frame of the outer box.

Claim 26 (currently amended): A sputtering target transport box according to claim 1, wherein a through-type hold is provided on the inner box to simplify removal of said inner box from said outer box.

Claim 27 (previously presented): A sputtering target transport box according to claim 26, wherein a cushion material is provided between the outer box and inner box.

Claim 28 (previously presented): A sputtering target transport box according to claim 1, wherein a cushion material is provided between the outer box and inner box.

Claim 29 (previously presented): A sputtering target transport box according to claim 1, further comprising a joint removably fixing the cover of the outer box to the outer frame of the outer box.

Claim 30 (currently amended): A sputtering target transport box according to claim 1, ~~further comprising a wherein said sputtering target inserted within is disc-shaped, brittle, and~~ made of a metal or ceramic material and said void of said inner sputtering target retention frame is of a disc-shape substantially matching the shape of the disc-shaped sputtering target.